

Home

Runxin

Location : Home >> Softener valve

Category

Multi-functional Flow..
Residential Softener
Fittings for Water..
Electronic Ball Valve..
Solar Energy / Water..
Products Introduction
Application Case

Softener valve

News information

63515 (F99A1) 63615(F99A3)

Product Centre

Hit : 120

Service support

Marketing

Contact us



Detail

Technical Parameters :

- Water pressure -----0.2—0.6MPa
- Water temperature -----5-50℃
- Transformer -----DC24V、1.5A
- Inlet/Outlet-----2" M
- Drain-----1.5" M
- Brine line connector-----3/4" M
- Riser pipe-----1-1/2" D-GB or 1.9" OD
- Base-----4"-8UN
- Water capacity-----15 m³/h

Product Characteristics :

- Adopt hermetic head faces with high degree pottery, corrosion resistance, perfect sealing.
- Adopt a set of valve core, big flow rate: Under 0.2MPa pressure drop, the water treatment capacity can reach 15m³/h.
- Control valve with single tank has no hard water outlet during regeneration.
- Electronic ball valve will control the brine refill with soft water, save salt and water.
- Time clock type and meter type optional, can be switched by program.
- top-mounted or side-mounted optional(match with side-mounted connector).
- Brine electronic ball valve will close during brine draw and slow rinse.
- LED screen display, button lock function.
- Retain parameter and remind setting after power recover.
- Interlock, signal output connector, remote handling connector, pressure relief connector.

Working Principle and Range of Application :

It adopts program to drive the motor to control valve core, based on time signal, volume signal or outlet water quality to regenerate, adopts time signal to automatically realize the exchange of functions like backwash, brine & slow rinse, brine refill and fast rinse, etc.

It is main used in boiler softening water system, soften device of RO Pre-treatment and ion exchange equipment, etc.

Up : [63620\(F111A3\) 53520 \(F111B\)](#) Down : [82602 \(F105\)](#)

[Alibaba](#) / [Huicong](#) / [Download](#) / [Contact us](#) / [Wenzhou water treatment system](#)

Copyright© : Wenzhou Runxin Manufacturing Machine Co., Ltd. Company Address: Jinger Road, Shatou Group, Linjiang, Lucheng District, Wenzhou, Zhejiang, China



82602 (F105)



63550(F96A1)
63650(F96A3)



63540 (F78A1)
63640 (F78A3)



63620 (F95A3)